

ANTARES

Code : 20729

Type : produit

Attribute set : COMBINAISON

Article > Product

Description

Name	ANTARES
Reference	4152
Article designation	RISK E2 VA PG - ANTARES Combinaison

Classification

Typology	MULTI-RISK CLOTHING
Range	BASIC RANGE
Main profession	INDUSTRY
Season	All Seasons
Brand	LMA WORKWEAR
Gender	MAN
Release status	IN STOCK
Model	Coverall

Article > Product sheet

Style

Basic cut	RHODIUM 4117
Length inseam	75 - 80cm
Magic hem	+ 5 cm
Tint	solid
Colour	Grey
Shade	Stone Grey
Open Size	S-XXXXL

Features

Matter	Majority Cotton
Main composition	79% cotton 20% polyester 1% antistatic carbon

Copyright © LEBEURRE

Fabric specificities	antistatic component flame retardant fabric treated against liquid chemicals
Weight	260 g/m²

Finishes

Topstitching	triple
Stopping points	red contrasting
Reflective tape	full sewn 5 cm
Piping	red on the front paw on the pocket flap(s)
Product specifications	2 detector door flanges protection against liquid chemicals ATEX zone
Branding	left sleeve transfer ATEX zone transfer

Belt

Belt features	elasticated waistband on the side and back

Pockets

Number of pockets	5
Front pocket (symmetrical)	Italian with flap
Left thigh pocket	plated closed by flap and hidden hollow snap button
Right back pocket	plated closed by flap and hidden hollow snap button
Kneepad pocket	1 position interior
Right chest pocket	plated closed by flap and hidden hollow snap button

Attributs

Collar	Rising
Main Zip	hidden hollow snap tab and button under paw
Sleeve cuffs	semi elasticated

Article > Marketing

Text

Short text	Multi-risk coverall with enhanced visibility and knee pad pockets - RISK E2 VA PG
Marketing Summary	This multi-risk coverall, compliant with RISK E2 VA PG standards, offers complete protection in multi-hazard environments. Designed for ATEX zones, it effectively protects you from liquid chemicals, molten metal splashes, heat, and flames. Its flame-retardant and antistatic fabric guarantees your safety against major industrial hazards, allowing you to work with peace of mind in the most demanding conditions. Finally, its EN 14404+A1 compliant knee pad pockets effectively protect your knees when working on the ground.
Web Technical Details	Composition: Satin 79% cotton 20% polyester 1% antistatic carbon - 260gr/m² Multi-risk: Specially designed for ATEX zones, this suit offers you simultaneous protection against five major hazards: it protects you against heat and flames (EN ISO 11612:2015, E2), spatter during welding and related techniques (EN ISO 11611:2015), liquid chemical substances (EN 1304:2005+A1:2009 Type 6), sparks

Copyright © LEBEURRE

	due to electrostatic charges (EN 1149-5:2018) and thermal hazards of electric arcs (EN 61482-2:2020). Protection and safety: Its internal, single-position knee pad pockets, compliant with EN 14404+A1 standards, protect your knees during prolonged work on the ground, in conjunction with the INOX 028300 knee pad. Enhanced visibility: Certified to EN ISO 17353:2020, its retroreflective strips increase your visibility in low-light conditions. Adjustable and comfortable: The semi-elasticated cuffs allow for a customized fit to minimize soiling. The elasticated waistband adds further comfort. Support and stability: Its elasticated waistband at the sides ensures a comfortable fit. Five belt loops stabilize the waistband during changes of position. Functional: Its numerous pockets facilitate daily organization: one chest pocket with a flap and button closure, two side pockets with flaps, one left thigh pocket with a flap and concealed snap button closure, and one right back pocket with a flap and concealed snap button closure. A clever detail: The magic hem can lengthen the leg by 5 cm, adapting to your height. Its closure is covered by a snap-fastened flap, protecting sensitive surfaces. The high collar provides complete protection against the many hazards of daily life. Two loops on the front allow you to slip in your detector.

Article > Standards and Approvals

Standards

Oeko-tex Standard 100	No
PPE certifications	EN 1149-5 EN 13034 + A1 EN ISO 11612 EN ISO 11611 EN 61482-2 EN 14404 + A1 EN 17353 EN ISO 13688 + A1
PPE protection category	3 - Fatal Risk
PPE performance level	1
PPE performance class	1 - protection contre les risques faibles (projection et chaleur faible)
PPE Performance Index	A1 B1 C1 D0 E2 F1
Type of PPE protection	B3
Number of washes	5
Maintenance tips	wash and iron inside out Ré imprégnation à chaque lavage No re-retardant treatment allowed

Article > Commerce and logistics

Logistics

Quantity per sales unit	1
Conditioning	1

VARIANTS

CODE	LABEL
4152SGRIS	
4152MGRIS	
4152LGRIS	
4152XLGRIS	

Copyright © LEBEURRE

41522XLGRIS
41523XLGRIS
41524XLGRIS

Copyright © LEBEURRE